Data Sheet Issue 10/2015

# **BYK-C 8003**

Reactive polymeric coupling agent for improving the mechanical properties of glass fiber reinforced, radical curing systems based on unsaturated vinylester and polyester resins.

## **Product Data**

## Composition

Mixture of surface-active substances

# **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Acid value: 18 mg KOH/g Density (20 °C): 0.98 g/ml Flash point: 24 °C

## **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

## **Storage and Transportation**

Do not store or transport above 40 °C. Moisture sensitive. Close container immediately after use.

# **Applications**

# **Thermoset**

### **Special Features and Benefits**

BYK-C 8003 has been developed specifically for use in radical curing, glass fiber reinforced unsaturated vinylester and polyester resin systems. The additive improves the mechanical properties of the component through increased fiber-matrix bonding. The extent of the improvement depends on the choice of the glass fiber and resin system.

### **Recommended Levels**

1-3 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The additive should be added to the resin shortly before the curing process. After being added, the resin system must be processed within a maximum of 24 hours. The length of time varies depending on the type of resin and quantity of additive.



### **BYK-C 8003**

Data Sheet Issue 10/2015







**BYK-Chemie GmbH** P.O. Box 10 02 45 46462 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, AND Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives.

AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological

progress or further developments. This issue replaces all previous versions – Printed in Germany