

## BYK-3902 P

Polyacrylate-based, powdered standard anti-cratering and leveling additive for powder coatings. Particularly suited to thin-layer powder coatings.

### Product data

#### Composition

Polyacrylate, adsorbed on silicon dioxide

#### Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density:	1.27 g/ml
Residue on ignition:	32 %
Acrylate content:	63 %
Delivery form:	powder

### Applications

#### Powder coatings

##### Special features and benefits

BYK-3902 P is an innovative leveling additive for powder coatings. Its excellent dispersibility promotes gloss and leveling in powder coatings and prevent seeds, craters and fish eyes.

##### Recommended use

Recommended for powder coatings based on epoxides, polyester/epoxide, polyester, polyurethane and acrylate. BYK-3902 P can be used in all common powder coating formulations and is particularly recommended for thin-layer powder coatings owing to its good dispersibility.

##### Recommended levels

0.5–1.5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

##### Incorporation and processing instructions

The additive is mixed with resin, hardener, pigments and other raw materials in a high-speed mixer and then extruded. Good dispersion of the additive by the extruder promotes gloss and leveling of the powder coating and prevents the formation of craters, fish eyes and seeds.



**Your local  
contact**

**BYK-Chemie GmbH**

Abelstraße 45  
46483 Wesel  
Germany  
Tel +49 281 670-0  
[info@byk.com](mailto:info@byk.com)  
[www.byk.com](http://www.byk.com)



Download  
our app:  
[byk.com/app](http://byk.com/app)

ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAC®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, NANOBYK®, OPTIBENT®, OPTIGEL®, PURABYK®, RECYCLOBYK®, RHEOBYK®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information contained herein is based on our current knowledge and experience. No warranties, guarantees and/or assurances of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. Any information about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. Contractual terms and conditions, in particular agreed product specifications, always take precedence. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. We reserve the right to make any changes and to update the information herein without notice.