Technical Information

ORTEGOL® LA 2

Description

ORTEGOL® LA 2 is a high performance additive, designed to significantly reduce aldehyde levels in automotive molded foams.

Key performance benefits

- Scavanges aldehydes, most effectively foamaldehyde
- Improves physical properties
- Negligible emissions

Typical properties*	
Appearance	Clear liquid
Viscosity at 21 °C	98 mPa·s
Calculated OH number	1290 mg KOH/g
Water solubility	Soluble

^{*} For actual ranges, please refer to the Certificate of Analysis (CoA) / Sales Specification.

Application

ORTEGOL® LA 2 is recommended for use in molded high resilience (HR) foam systems in combination with our DABCO® NE range of negligible emission catalysts.

Formulation optimization may be required; ORTEGOL® LA 2 improves foam properties, hence, lower levels of cell opener and cross linker are required.

ORTEGOL® LA 2 can be added to a formulated system. Alternatively, it can be blended into an activator batch.

Common use level of ORTEGOL® LA 2 is 0.4 parts per 100 parts of polyol. The optimal concentration will depend on specifics of the formulation. Machine trials are highly recommended.

Storage recommendations

- Shelf life: minimum 3 months. For exact date of expiration, please consider CoA.
- Storage conditions: dry and cool place in factory-packed containers.
- Optimum storage temperature: 10 to 30 °C.

Safety instructions

Please consult the Safety Data Sheet for summary of product hazards, personal protective measures, and emergency release procedures.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Evonik Operations GmbH

Rellinghauser Straße 1–11 45128 Essen, Germany Phone: +49 201 173 3006 Email: polyurethane@evonik.com



For any further information, contact either your regional sales or technical support or visit our customer portal explorepu.evonik.com.

