

## Product information

# ANCAREZ<sup>®</sup> 4305

## Epoxy Resin

### DESCRIPTION

Ancarez 4305 epoxy resin is a low viscosity mono functional diluted Bis A/F diglycidyl ether resin designed for use at ambient temperature applications.

### TYPICAL PROPERTIES

Property	Value	Unit	Method
Appearance	Pale amber liquid		
Colour	max 2	Gardner	DIN ISO 4630
EEW	180-198	g/ Eq	EEW DIN 16945
Viscosity @ 25°C	700-1100	mPa.s	Rotary viscometer DIN 53019 part 1
Specific Gravity @ 25°C	1.13	g/cm <sup>3</sup>	ASTM D93
Flash Point	> 130	°C	

### ADVANTAGES

- Very Low viscosity
- Low crystallization tendency

### APPLICATIONS

- Industrial Protective and Maintenance Coatings
- Marine Coatings
- Self leveling floors and screed mortars
- Crack Injection systems
- Composites

### SHELF LIFE

At least 36 months from the date of manufacture in the original sealed container in a cool and dry place.

## STORAGE AND HANDLING

Refer to the Safety Data Sheet for Ancarez 4305.

Ancarez® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

### Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

#### EVONIK OPERATIONS GMBH

Business Line Crosslinkers  
Paul-Baumann-Str. 1  
45764 Marl  
Germany

[www.evonik.com/crosslinkers](http://www.evonik.com/crosslinkers)

**Product Information:** [APCSE@evonik.com](mailto:APCSE@evonik.com)

**Sample Request:** [APCSE@evonik.com](mailto:APCSE@evonik.com)

#### EVONIK CORPORATION

Business Line Crosslinkers  
7001 Hamilton Boulevard  
Trexlerstown, PA 18087  
USA

[CrosslinkersProinfo@evonik.com](mailto:CrosslinkersProinfo@evonik.com)

[Crosslinkers-Samples@evonik.com](mailto:Crosslinkers-Samples@evonik.com)

#### EVONIK SPECIALTY CHEMICALS (SHANGHAI) CO., LTD.

Business Line Crosslinkers  
55, Chundong Road  
Xinzhuang Industry Park  
Shanghai, 201108  
China

[CL-Asiainfo@evonik.com](mailto:CL-Asiainfo@evonik.com)

[CL-Asiainfo@evonik.com](mailto:CL-Asiainfo@evonik.com)

