

BYK-A 501 SG

Silicone-free air release additive for unsaturated polyester resins and particularly for polyurethane and epoxy systems.

Product data

Composition

Solution of polyolefin

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C):	0.89 g/ml
Flash point:	46 °C
Refractive index (20 °C):	1.500
Turbidity:	< 10 TE/F
Hazen color number:	< 200

Applications

Thermosets

Special features and benefits

BYK-A 501 SG is a highly effective air release additive for virtually all unsaturated polyester resins and processing techniques and is also recommended for epoxy resin systems.

Recommended use

Particularly recommended for unsaturated polyester resins and epoxy resins, gel coats and casting systems.

Recommended levels

0.1–0.5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

Stir in the resin before adding other components. In some resins, air release additives may cause haze in the finished part.

**Your local
contact****BYK-Chemie GmbH**
Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735**info@byk.com**
www.byk.com

ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK®-DYNWET®, BYK-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.