

CLAYTONE-II

Economy rheological additive for diesel-based drilling fluids to increase the carrying capacity and hole cleaning capabilities.

Product Data

Composition

Alkyl quaternary ammonium bentonite

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Sieve passing (200 mesh/74µm): 85 %
Specific Gravity: 1.6
Loss on ignition (1 h, 1000 °C): 37 %
Bulk density: (26 lb/ft³) 416 kg/m³
Supplied as: Free-flowing powder in 50-lb bags

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

Moisture sensitive. Pallet stacking should be no more than two pallets high in order to prevent compaction.

Applications

Oil-Based Drilling Fluids

Special Features and Benefits

CLAYTONE-II is an economy grade, organo-modified clay rheological additive recommended for use in oil based muds. In addition to imparting excellent rheological properties, it increases the carrying capacity and hole cleaning capabilities of the drilling fluid. CLAYTONE-II also has the secondary benefits of improving filtration control and emulsion stability.

Recommended Use

CLAYTONE-II is recommended for drilling fluids utilizing diesel as the base oil and where the bottom hole temperatures will not exceed 350 °F (175 °C).

Example formulation: 11.0 pounds/gallon 75/25 Diesel Results of aging test

	350 ml formulation	Multi-mixer at 11,000 rpm
Diesel #2	218 ml	
CLAYTONE-II	6 g	Mix 5 min.
Lime	3 g	Mix 5 min.
EnvaMul™ 1699 *	4 g	Mix 5 min.
CaCl ₂ (25 % in water)	79 ml	Mix 20 min.
Barite	150 g	Mix 5 min.
OCMA (drill solids)	20 g	Mix 5 min.
Silverson homogenizer at 6,000 rpm		Shear 5 min.

* EnvaMul™ 1699 is a product of MWV Specialty Chemicals

figure 1

Properties (at 120 °F)	Initial	After Hot Rolling	
		16 h at 150 °F	16 h at 250 °F

Rheological properties

600 rpm reading	50	60	57
300 rpm reading	34	41	38
200 rpm reading	27	34	30
100 rpm reading	20	25	22
6 rpm reading	10	14	12
3 rpm reading	8	12	9
Plastic Viscosity (cP)	16	19	19
Yield Point (lb/100 ft ²)	18	22	19

Electrical Stability

Peak Volts	592	722	603
------------	-----	-----	-----

figure 2

Recommended Levels

A 2-8 lb/barrel (5.7-23 kg/m³) addition is typically used for most conventional oil-based invert drilling fluids. Actual CLAYTONE-II usage will depend on the base oil, oil/water ratio, solids, and the emulsifier package. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

CLAYTONE-II requires high shear mixing and temperature to fully yield. A small stream of water can be used to reduce yield time. (The water phase of invert emulsions provides the polar activation).



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYPK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAC®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera. SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany