

Data sheet Issue 11/2023

RHEOBYK-7590 PC

Vegan, organic rheology additive based on a natural castor oil derivative for oil phases in personal care applications. Provides thixotropic stabilization and high thickening (COSMOS APPROVED, NATRUE Approved).





Product data

Composition

Castor oil derivative (INCI: Trihydroxystearin)

Vegan

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 1.02 g/ml Melting range: 84–88 °C Sieve passing (325 mesh/44 μ m): min. 99 %

Acid value: max. 4 mg KOH/g
OH value: 155–164 mg KOH/g
Iodine value: max. 4 g/100 g
Saponification value: 176–182 mg KOH/g

Color: white

Delivery form: free-flowing powder

Storage and transportation

RHEOBYK-7590 PC should be transported and stored dry in unopened original packaging at temperatures between 0 $^{\circ}$ C and 30 $^{\circ}$ C.

Applications

Personal care

Special features and benefits

RHEOBYK-7590 PC stabilizes pigments in suspensions and improves the thermal stability of waxy formulations. In addition, the additive serves to thicken medium- to low-polar or aliphatic solvents (especially typical cosmetic oils), to stabilize water-in-oil emulsions and to regulate the flow behavior and yield point of formulations. It is translucent when dissolved and produces a very soft skin-feel, resulting in appealing sensory properties. Additionally, it can be used as an emollient, conditioning agent and water repellent. The additive is especially recommended for thickening and stabilizing natural cosmetic formulations.

Data sheet Issue 11/2023

Recommended use

Creams and lotions	
Sunscreen products	
Hair styling products	
Liquid makeup	
Lipsticks	
Lip glosses	
Pressed powders	
Antiperspirants/deos	
especially recommended recommended	

Recommended levels

1–7 % additive (as supplied) based on the total formulation, depending on the rheological properties desired.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

RHEOBYK-7590 PC should be added to the oil phase at the beginning of the dispersion process, preferably by pre-mixing for 5–10 minutes with the solvent or oil.

The effectiveness of the additive is sensitive to temperature and system polarity. For optimal performance, RHEOBYK-7590 PC should be fully activated by mixing the formulation at a temperature of 35–65 °C for 20 minutes with high shear forces. If the temperature is too low or exceeds the maximum activation temperature of 65 °C, seeding (building of soft gel-like particles) may occur. In this case, it is recommended to rework the formulation by heating to 55–65 °C and stirring with high shear. The formulation should be stirred during cooling to prevent recrystallization.









BYK-Chemie GmbHAbelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com www.byk.com ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-AQUAGEL®, BYK®-DYNWET®, BYK-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKIET®, BYKO2BLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINIERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.