

CERAFLOUR 950

Micronized wax based on modified HDPE for solvent-borne and solvent-free coatings and printing inks as well as powder coatings to improve the scratch resistance, soft-feel effect and matting. The additive is particularly suitable for radiation-curable formulations.

Product Data

Composition

Micronized, modified HD polyethylene wax

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density:	0.95 g/cm ³	
Melting point:	135 °C	
Particle size distribution (laser diffraction, volume distribution):	D50: 9 µm	D90: 15 µm
Supplied as:	Micropowder	

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

Temperature sensitive. To be stored and transported at a temperature below 50 °C.

Applications

Liquid Coatings

Special Features and Benefits

The additive improves scratch resistance, creates a soft feel effect and has a matting effect. Main application area – solvent-free, radiation-curable coating systems.

Recommended Levels

1-10 % additive (as supplied) based on the total formulation, depending on the desired gloss level.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive is preferably incorporated into the coating at the end of the production process at a moderate shear rate.

Printing Inks and Overprint Varnishes

Special Features and Benefits

The additive increases surface slip and improves abrasion resistance in solvent-free, radiation-curable printing inks and overprint varnishes.

Recommended Levels

0.1-0.3 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive is preferably incorporated into the coating at the end of the production process at a moderate shear rate.

Powder Coatings

Special Features and Benefits

The additive is recommended for matting powder coatings and it also improves surface protection.

Recommended Use

CERAFLOUR 950 is recommended for powder coatings based on polyester, polyester/epoxide, acrylate, polyurethane and epoxides.

Recommended Levels

0.5-2 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

CERAFLOUR 950 should be mixed with resin, hardener, pigments and other additives using a high-speed mixer and extruded along with all components.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAX®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYPK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, PRIEX®, PURE THIX®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany