

BYK-1790

Silicone-free, polymer-based defoamer for solvent-free, radiation-curing wood and industrial coatings, printing inks and adhesives. Suitable for pigmented and unpigmented coating systems.

Product Data

Composition

Polyolefin

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.85 g/ml

Non-volatile matter (10 min., 150 °C): 100 %

Applications

Coatings and Printing Inks

Special Features and Benefits

BYK-1790 is silicon-free and is recommended for solvent-free, radiation-curing (UV and ESH) coating systems (pigmented and unpigmented), printing inks and overprint varnishes. The high efficiency of the defoamer is not impacted by pigments, fillers, wax additives or matting agents.

Recommended Levels

0.1-0.7 % additive (as supplied) based upon the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

Due to its high incompatibility, the defoamer must be incorporated at high shear forces (in the mill base) to ensure good distribution. Otherwise defects may occur in the system.

Adhesives & Sealants

Special Features and Benefits

BYK-1790 is silicon-free and is recommended for solvent-free, radiation-curing (UV and ESH) adhesives (pigmented and unpigmented) as well as for reactive polyurethane hot melt adhesives. It has no negative effect on the adhesive properties of the adhesives. In radiation-curing formulations, BYK-1790 is ideal for universal use in acrylate based binders. It prevents foaming in the manufacture of reactive polyurethane hot melt adhesives even at high viscosity. Significantly shorter evacuation times lead to an increase in the efficiency of production due to the additive.

Recommended Levels

0.1-0.7 % additive as supplied based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

Due to its high incompatibility, the defoamer must be incorporated at high shear forces (in the mill base) to ensure good distribution. Otherwise defects may occur in the system.



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAC®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.