

BYK-3950 P

Wax-based powdered processing additive with pigment-affinic groups for powder coatings. It improves pigment and filler dispersion and processing, leveling and degassing.

Product data

Composition

Modified wax

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 1.00 g/ml Active substance: 100 % Supplied as: powder

Storage and transportation

Temperature sensitive. To be stored and transported at a temperature below 50 °C.

Applications

Powder coatings

Special features and benefits

As a result of its pigment-affinic groups, the dispersion of solid particles is improved and higher filler and pigment contents are possible. Leveling (DOI – distinctness of image) is improved and use of this product – specifically in HAA systems – results in better degassing of the powder coating.

Recommended levels

0.5–2 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive is mixed with resin, hardener, pigments and other raw materials in a high-speed mixer and then extruded. Good dispersion of the additive by the extruder promotes gloss and leveling of the powder coating and prevents the formation of craters, fish eyes and seeds.

Special note

The processing additive should always be used in combination with a standard leveling additive.

BYK-3950 P

Data sheet Issue 09/2022







BYK-Chemie GmbH

46483 Wesel Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com www.byk.com

ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-AQUAGEL®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKOZBLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAFLOUR®, CERATIX®, CLAYTONE®, CLOSITE®, DISPERBYK®, DISPERBYLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.