

Polyurethane thickener

TEGO® Viscoplus 3060

DESCRIPTION

TEGO® Viscoplus 3060 is a pH-independent, associative thickener with strongly pseudoplastic flow behavior.

KEY BENEFITS

- provides pseudoplastic (shear thinning) flow behavior
- applicable in a broad range of waterborne coatings
- APEO- and tin-free

EFFECT

Structure viscosity



Sagging prevention



Settling prevention



Drag resistance



Spattering prevention



TYPICAL APPLICATIONS

- Architectural paints
- Pigment concentrates
- Wood coatings

TECHNICAL DATA

active matter content	approx. 60 %
appearance	clear to hazy liquid
chemical description	non-ionic polyurethane solution
solvent	water

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

PROCESSING INSTRUCTIONS

- Addition to the coating also possible after production.
- Addition to the coating as supplied or as a predilution is possible.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

SUITABILITY

waterborne	solventborne
●	●
●	●
●	●

● not suitable ● partly suitable ● suitable

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com