

AQUACER 570

Modified Ecolabel-conform sunflower wax emulsion to improve the surface properties of care products and polishes.

Product Data

Composition

Non-ionic emulsion of a sunflower/carnauba wax blend

**VOC-free (< 1500 ppm),
Ecolabel-conform**

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Non-volatile matter (1 h, 125 °C): 40 %
Carrier: Water
Melting point (wax content): 85 °C
Viscosity (23 °C, D=800/s): < 50 mPa·s
pH value: 5.0

Storage and Transportation

Temperature sensitive. To be stored and transported between 5 °C and 35 °C. Mix well before use.

Special Note

AQUACER 570 is Ecolabel-conform.

Applications

Care Products and Polishes

Special Features and Benefits

AQUACER 570 seals and thereby covers any minor scratches on the surface that is to be treated, and restores the surface's original color. The melting point of 85 °C means that the wax emulsion can easily be polished using a soft cloth (e.g. microfiber cloth), even when using mechanical tools. AQUACER 570 improves the hydrophobicity and the oleophobicity of care products and polishes.

Recommended Use

AQUACER 570 is recommended for maintaining and protecting all types of surfaces, for leather, coated and uncoated surfaces.

Leather care products	<input checked="" type="checkbox"/>
Car maintenance products	<input checked="" type="checkbox"/>
Furniture polishes	<input checked="" type="checkbox"/>

☒ especially recommended ☐ recommended

Recommended Levels

3-15 % additive (as supplied) based on the total formulation.

A higher dosage is possible, however the polishability must be checked in this case.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be incorporated during any stage of the production process whilst stirring. Further surface-active substances must be added at the end of the process, as otherwise the care product formulation has a tendency to foam.

Special Note

It is possible to combine the product with other wax emulsions to increase the performance of the care product formulation.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany