

AQUACER 561

Beeswax-based wax emulsion to improve surface protection in aqueous care products and coating systems.

Product Data

Composition

Non-ionic aqueous beeswax emulsion

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Non-volatile matter: 25 %
 Carrier: Water
 Melting point (wax content): 65 °C
 pH value: 6.5

Storage and Transportation

Temperature sensitive. To be stored and transported between 5 °C and 35 °C. Mix well before use.

Applications

Care Products and Polishes

Special Features and Benefits

AQUACER 561 is used as the main component in aqueous care products and polishes. Mixtures with other wax emulsions (e.g., carnauba wax) to optimize the properties are standard. AQUACER 561 covers any minor scratches and restores the color of the surfaces. The low melting point of beeswax makes it possible to polish using a soft cloth without mechanical tools.

Recommended Use

Furniture polish	■
Plastic care product	■
Wooden floorboards and cork	■
Leather care / shoe polish	■
Car polish	□

■ especially recommended □ recommended

Incorporation and Processing Instructions

The wax additive is preferably added with stirring after blending the polymers with the plasticizers and water, although before incorporating surface-active substances.

Special Note

Surface-active substances to optimize surface wetting (e.g. BYK-349 or BYK-3455 in combination with BYK-DYNWET 800) should be added at the end of the production process.

Coatings Industry

Special Features and Benefits

The additive improves water repellency and anti-blocking in aqueous coatings.

Recommended Levels

4-8 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive should preferably be post-added to the coating using a low shear rate. Mix well before use.



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAX®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.