

TEGO® Wet 570 Terra

DESCRIPTION

TEGO® Wet 570 Terra is a highly surface active biosurfactant. It improves substrate, pigment, and filler wetting and shows outstanding performance in anti-cratering.

KEY BENEFITS

- highly suitable for waterborne coatings and inks
- especially for coatings with a high sustainability profile

EFFECT

Pigment wetting



Substrate wetting



Anti-crater effect



Reduction of static surface tension



Reduction of dynamic surface tension



SUITABILITY

waterborne



solventborne



2-pack 100%



radiation-curing



pigmented coatings



clear coatings



● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Architectural paints
- Pigment concentrates
- Wood coatings
- General industrial coatings
- Printing Inks

TECHNICAL DATA

active matter content	45 %
appearance	yellowish clear liquid
chemical description	solution of glycolipids in water

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

PROCESSING INSTRUCTIONS

- Addition to the grind is recommended in pigmented formulations.
- Suitable for addition during the let-down or even in clear formulations.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 12 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com