

**DESCRIPTION**

ACEMATT® OK 607 is a fine particle sized wax-treated precipitated silica. It is suitable for pigmented and non-pigmented systems.

**KEY BENEFITS**

- very low viscosity impact
- high surface smoothness
- very high sheen

**EFFECT****Matting efficiency****Transparency****Viscosity****Smoothness/Haptic****Sedimentation behavior****TYPICAL APPLICATIONS**

- Plastic coatings
- Car OEM coatings
- Wood coatings
- Printing Inks

**TECHNICAL DATA**

<b>carbon content</b>	5.5 %
<b>DOA absorption</b>	250 ml/100g
<b>Grindometer value</b>	16 µm
<b>particle size, d<sub>50</sub></b>	4.4 µm
<b>pH-value</b>	6.3
<b>specific surface area (N<sub>2</sub>)</b>	130 m <sup>2</sup> /g

**RECOMMENDED ADDITION LEVEL**

As supplied calculated on total formulation: 1.5 - 7.0 %

**PROCESSING INSTRUCTIONS**

Addition to the coating as supplied or as a predilution is possible.

**HANDLING & STORAGE**

When stored in an original unopened packaging, the product has a shelf life of 24 months from the date of manufacture. We recommend to store the product in closed containers under dry conditions and to protect the material from volatile substances.

**SUITABILITY**

waterborne	solventborne
radiation-curing	2-pack coatings
high solids	pigmented coatings
clear coatings	
not suitable  partly suitable  suitable	

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)