

CERAFLOUR 1010

Bio-based, micronized rape seed wax. Suitable for use in aqueous, solvent-based, solvent-free and UV systems to achieve a high level of matting and improve mechanical properties.

Product data

Composition

Micronized rape seed wax

VOC-free (< 1500 ppm)
BRC content: 100 %

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C):	0.91 g/cm ³
Melting point:	70 °C
Particle size distribution D50:	6 µm
Particle size distribution D90:	16 µm
Bio-based carbon content (ASTM D6866):	100 %
Delivery form:	Micropowder

Storage and transportation

Temperature sensitive. Do not store and transport above 30 °C. CERAFLOUR 1010 is biobased and therefore sensitive to microbial contamination when stored in open containers in a humid environment. During storage, the particles of CERAFLOUR 1010 can agglomerate. This effect is increased at elevated temperatures. The agglomerates can be broken by using stronger shear forces for the incorporation of the product.

Applications

Coatings industry

Special features and benefits

CERAFLOUR 1010 increases scratch and abrasion resistance. The additive has a strong matting effect and can be incorporated in all systems. It has no effect on viscosity. The polymer ensures, especially in solvent-free and UV systems, a very homogeneous and smooth surface. CERAFLOUR 1010 is bio-based and consists of 100 % renewable raw materials

Recommended use

Wood and furniture coatings	■
General Industrial Coatings	■
Architectural coatings	■

■ especially recommended □ recommended

Recommended levels

0.5–10 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive should preferably be incorporated into the coating at the end of the production process at high shear rate. Aqueous slurries of CERAFLOUR 1010 that are not processed immediately must be protected against microbial contamination with suitable preservatives.

Special note

When using the additive in solvent-based systems, the compatibility of the product in the particular solvents used must be tested.



**Your local
contact**

BYK-Chemie GmbH
Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFLO®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.