Product information

ANCAMIDE® 3178

Curing Agent

DESCRIPTION

Ancamide 3178 curing agent is a polyamide adduct supplied at 75% solids in xylene. The curing agent is recommended for use with liquid epoxy resins for the formulation of solvent based and high solid protective coatings.

TYPICAL PROPERTIES

Property	Value	Unit	Method
Appearance	Clear amber liquid		
Colour	≤ 10	Gardner	ASTM D 1544-80
Viscosity @ 25°C	1800-5900	mPa.s	Brookfield RVTD, Spindle 4
Amine Value	235-266	mg KOH/g	Perchloric Acid Titration
Solids	75+/-2	%	
Specific Gravity @ 21°C	0.97		
Equivalent	150-160	Wt/{H}	
Recommended use Level	80-85	PHR	With liquid Bisphenol A diglycidyl ether (EEW=190)

ADVANTAGES

- · Good compatibility with liquid resin
- Corrosion resistance

APPLICATIONS

Solvent based coatings with high solid contents

SHELF LIFE

At least 24 months from the date of manufacture in the original sealed container at ambient temperature. Store away from excessive heat and humidity in tightly closed containers.



STORAGE AND HANDLING

Refer to the Safety Data Sheet for Ancamide 3178 curing agent.

TYPICAL HANDLING PROPERTIES

Property	Value	Unit
Typical cure schedule	2-7	days

Ancamide® is a registered trademark of Evonik Industries AG or one of its subsidiaries.

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

EVONIK OPERATIONS GMBH

Business Line Crosslinkers Paul-Baumann-Str. 1 45764 Marl Germany

www.evonik.com/crosslinkers

Sample Request: APCSE@evonik.com Crosslinkers-Samples@evonik.com

EVONIK CORPORATION

Business Line Crosslinkers 7001 Hamilton Boulevard Trexlertown, PA 18087 USA

EVONIK SPECIALTY CHEMICALS (SHANGHAI) CO., LTD.

Business Line Crosslinkers 55, Chundong Road Xinzhuang Industry Park Shanghai, 201108 China

CL-Asiainfo@evonik.com CL-Asiainfo@evonik.com

